

Anti-tack TP 130

Batch off Soap

ANTI-TACK TP 130 is used for the treatment of unvulcanised rubber compounds in the form of sheet or strip to prevent surface sticking.

ANTI-TACK TP 130 is powder type Antitack agent. It is non dusting and non foaming

PROPERTIES

Chemical Characteristics : Mixture of anti adhesive

Appearance : non dusting, yellowish powder

Specific gravity : approx.1.03 g/cm³

Dilution ratio : 1:15 (Anti-tack TP 130: H₂O)

Storage Stability : 2 years under cool and dry storage conditions in orginally packing

Packing : Paper bags containing 30 kg net

Tepe Kimya (M) SDN. BHD.

Plo 602 Jalan MIEL 1 Off Jalan Keluli 9
81700 Pasir Gudang Johor MALAYSIA
Tel: +60 7 251 7844 Fax: +60 7 251 7848

Web: www.tepekimya.com

Tepe Kimya San. ve Tic.Ltd.Şti.

Kimyacılar Organize Sanayi Bölgesi
Melek Aras Bulvarı N:12 34959
Tepeören Tuzla İstanbul/TURKEY
Tel:+90 216 5931920 Fax:+90 216 5931925

Tepe Trade Intl. Chem Pte. Ltd.

63 Mount Sinai Drive #05-01
277116 SINGAPORE
Tel:+65 932 65813 Fax: +65 631 48 435

Email: info@tepekimya.com