



STAB TP 2909

Lead based one pack stabilizer

DESCRIPTION

Lead based complex stabilizer.

This stabilizer is particularly suitable for the manufacture of Wall Panell, & Sheet STAB TP 2909 is also used in the other rigid PVC processes. It is very effective heat stabilizer. It has a very well balanced internal and external lubrication. Suitable for all types of injection moulding machines and imparts good welding properties, smooth surface and dimentional stability to the products.

PROPERTIES

FORM	: Flake
COLOUR	: White Cream
ASH CONTENT	: % 21,5 ± 2
LEAD CONTENT	: % 20 ± 2
MOISTURE	: % 1.0 max.
BULKDENSITY	: 500 ± 30 g/l

APPLICATION

Wall Panell Sheet

RECOMMENDED CHARGES

4.0 - 7.0 phr depending on the processing conditions and the type of the materials to be produced.

PACKING: 25 kg net paper bags

Tepe Kimya (M) SDN. BHD.

Plo 602 Jalan MIEL 1 Off Jalan Keluli 9 81700 Pasir Gudang Johor MALAYSIA Tel: +60 7 251 7844 Fax: +60 7 251 7848 **Web:** www.tepekimya.com

Tepe Kimya San. ve Tic.A.Ş..

2. Oragnize Sanayi Bölgesi
7. Cadde No : 11
Hendek – SAKARYA
Tel:+90 216 5931920 Fax:+90 216 5931925

Tepe Trade Intl. Chem Pte. Ltd.

63 Mount Sinai Drive #05-01 277116 SINGAPORE Tel:+65 932 65813 Fax: +65 631 48 435 **Email:** info@tepekimya.com